

| Model | Zakres kątów cięcia | Maksymalne wymiary ciętego materiału [mm] | Wymiar brzeszczotu [mm] | Prędkość liniowa brzeszczotu [m/min] | Moc [kW] | Ciężar maszyny [kg] |
|--|---------------------|---|-------------------------|--------------------------------------|----------|---------------------|
| Przecinarki sterowane ręcznie MO | | | | | | |
| PMS 100/150 MO | 90°,45° | ●100, ■100x150 | 13x0,65x1470 | 54 | 0,37 | 23 |
| PMS 170/210 MO | 90°,45°,60° | ●170, ■170x170, ■210x170 | 20x0,90x2100 | 40/80 | 0,74 | 156 |
| PMS 230/260 MO | 90°,45°,60° | ●227, ■220x220, ■260x110 | 27x0,90x2455 | 36/72 | 1,10 | 216 |
| Półautomaty ramieniowe skrzętne SAD | | | | | | |
| PMS 180/230 SAO | 90°,45°,60° | ●178, ■178x178, ■225x110 | 20x0,90x2265 | 30/60 | 0,74 | 165 |
| PMS 230/260 SAD | 90°,45°,60°,45°(L) | ●227, ■220x220, ■260x110 | 27x0,90x2455 | 36/72 | 1,10 | 280 |
| PMS 250/310 SAD | 90°,45°,60°,45°(L) | ●250, ■240x240, ■310x230 | 27x0,90x2730 | 36/72 | 1,10 | 310 |
| PMS 270/350 SAD | 90°,45°,60°,45°(L) | ●270, ■260x260, ■350x220 | 27x0,90x3180 | 34/68 | 1,50 | 360 |
| Półautomaty ramieniowe skrzętne z imadłem hydraulicznym HAD | | | | | | |
| PMS 230/260 HAD | 90°,45°,60°,45°(L) | ●227, ■220x220, ■260x110 | 27x0,90x2455 | 36/72 | 1,10 | 380 |
| PMS 250/310 HAD | 90°,45°,60°,45°(L) | ●250, ■240x240, ■310x230 | 27x0,90x2730 | 36/72 | 1,10 | 410 |
| PMS 270/350 HAD | 90°,45°,60°,45°(L) | ●270, ■260x260, ■350x220 | 27x0,90x3180 | 34/68 | 1,50 | 460 |
| PMS 330/510 HAD | ± 60°(L,R) | ●331, ■320x485, ■260x510 | 34x1,10x4180 | 26-80 | 2,20 | 850 |
| PMS 330/460 HAD | ± 60°(L,R) | ●330, ■305x305, ■305x460 | 27x0,90x4115 | 25/45/70/100 | 2,20 | 800 |
| PMS 400/620 HAD | ± 60°(L,R) | ●400, ■400x400, ■400x620 | 34x1,10x4900 | 25/45/70/100 | 3,70 | 1400 |
| PMS 460/600 HAD | ± 60°(L,R) | ●460, ■460x460, ■445x600 | 41x1,30x5330 | 26-80 | 3,70 | 1320 |
| PMS 460/600 HADP | ± 60°(L,R) | ●460, ■460x460, ■440x600 | 41x1,30x5330 | 26-80 | 3,70 | 1370 |
| Automaty jednokolumnowe HCN | | | | | | |
| PMS 360/360 HCN | 0° | ●360, ■360x360 | 34x1,10x4420 | 18-90 | 3,70 | 1650 |
| PMS 460/820 HCDP | ± 60°(L,R) | ●460, ■460x460, ■500x700 | 41x1,30x5450 | 17/25/35/45/65/75 | 5,60 | 2270 |
| PMS 500/700 HCN | 0° | ●500, ■500x500, ■500x700 | 41x1,30x5450 | 17/25/35/45/65/75 | 5,50 | 2400 |
| PMS 700/800 HCN | 0° | ●700, ■700x700, ■700x800 | 54x1,60x7600 | 15-70 | 7,50 | 5500 |
| PMS 1000/1000 HCN | 0° | ●1000, ■1000x1000 | 67x4,60x8800 | 15-70 | 11,20 | 9500 |
| PMS 1300/1300 HCN | 0° | ●1300, ■1300x1300 | 80x1,60x12300 | 15-70 | 15,00 | 16000 |
| Automaty ramieniowe AN/AD | | | | | | |
| PMS 250/300 ANS | 0° | ●250, ■250x250, ■250x300 | 27x0,90x3505 | 22-75 | 2,20 | 1430 |
| PMS 250/300 AN | 0° | ●250, ■250x250, ■250x300 | 27x0,90x3505 | 22-75 | 2,20 | 1430 |
| PMS 330/330 AN | 0° | ●330, ■330x330 | 34x1,10x4100 | 17-71 | 3,70 | 1700 |
| PMS 350/620 AD | ± 60°(L,R) | ●350, ■350x350, ■350x320 | 34x1,10x4900 | 20-100 | 3,70 | 2200 |
| PMS 420/415 AN | 0° | ●420, ■415x415 | 41x1,30x4770 | 15-75 | 5,60 | 2250 |
| PMS 460/460 AN | 0° | ●460, ■360x360, ■360x460 | 41x1,30x4670 | 20-100 | 5,50 | 2400 |
| Automaty jednokolumnowe ACN | | | | | | |
| PMS 260/310 ACN | 0° | ●260, ■260x160, ■260x310 | 34x1,10x3920 | 20-100 | 3,70 | 1750 |
| PMS 360/360 ACN | 0° | ●360, ■360x360 | 34x1,10x4420 | 18-90 | 3,70 | 2000 |
| PMS 460/500 ACN | 0° | ●460, ■460x460, ■460x500 | 41x1,30x5450 | 18-90 | 5,50 | 3600 |
| PMS 560/615 ACN | 0° | ●560, ■560x560, ■560x615 | 54x1,60x6600 | 19-90 | 7,50 | 4500 |
| PMS 650/700 ACN | 0° | ●650, ■650x650, ■650x700 | 54x1,60x7600 | 15-75 | 7,50 | 6000 |
| PMS 700/800 ACN | 0° | ●700, ■700x700, ■700x800 | 54x1,60x8000 | 15-75 | 7,50 | 7000 |
| Przecinarka dwukolumnowa sterowana numerycznie ACP | | | | | | |
| PMS 460/460 ACP | 0° | ●460, ■460x460 | 41x1,30x5450 | 15-75 | 7,50 | 4500 |
| Przecinarki tarczowe | | | | | | |
| PMS 65/52 CSHS | 0° | ●15-65, ■15-52 | Ø280xT2,0 | 30-150 RPS | 7,5 | 1800 |
| PMS 100/80 CSHS | 0° | ●20-100, ■20-80 | Ø360xT2,5 | 30-130 RPS | 11 | 2500 |
| PMS 150/110 CSHS | 0° | ●70-150, ■70-110 | Ø460xT2,7 | 30-130 RPS | 15 | 3500 |